

Flaring device DN 25

Safe and reliable • sturdy and suitable for construction sites
• efficient • low-maintenance



Area of use



Residual gas quantities should be removed from the working area of a blocked, shut-down supply line or a supply line filled with a new medium. For an environmentally conscious corporate philosophy, these should be flared to avoid methane emissions.



Product description

Our flaring device has been developed for safe and trouble-free use and is optionally available with a Venturi nozzle. The piezo burner enables safe ignition of the pilot flame. The connections to the degassing hose are conically sealing by means of an NBR O-ring. The GRS25 from IBEDA (certified by the DVGW (German Technical and Scientific Association for Gas and Water) is fitted as a safety device (flame arrester/gas backflow safety device). This prevents the dangerous build-up of gaseous mixtures on the inlet side and any potential flashback.



ECO-Standard	PREMIUM-Standard	PREMIUM-PRO
Safety device consisting of . . .		
Brass without venturi nozzle Artikel-Nr.: 9020000	Stainless steel without venturi nozzle Artikel-Nr.: 9020005	Stainless steel with venturi nozzle Artikel-Nr.: 9020015

- Overall height of 2245 mm/2170 mm
- Manufactured from stainless steel 1.4301
- DN 25 (1"), glass-bead blasted
- Tripod with three legs
- Includes extensive accessories (adapter, ground pegs, pressure gauge)
- Degassing hose PN 20 GWPB ISO 3821 (EN 559)
- Weight: 15 kg flaring device, 15 kg transport trolley including accessories
- Pressure range: 5 mbar to 5 bar for natural gas, propane and biogas
- For hydrogen, suitable up to 1.5 bar*
- Four different versions
- Gas backflow safety device GRS25
- Temperature range: -20 °C—+70 °C
- Side connection for concentration measurements
- Flow at 1 bar mains pressure approx. 250 m³/h IN (depending on detail)
- Aspirated line volume via Venturi nozzle at 12 bar compressor pressure approx. 100 m³/h IN

* separate degassing hose needed

